


Schottnippel Serie M mit metrischem Außengewinde

Betriebsdruck: -0,95 – 25 bar
 Temperaturbereich: -20 °C bis +120 °C



Anschluss	L1	L2	D	SW1	SW2	Artikel-Nr.	
						MS	MSV
M 5 i	15	11,5	M 10 x 1	13	13		
G 1/8 i	22	15	M 14 x 1,5	17	17		
G 1/4 i	24	17	M 20 x 1,5	24	24		
G 3/8 i	27	18,5	M 24 x 1,5	27	27		
G 1/2 i	31	20,5	M 30 x 1,5	36	36		



Kontermutter Serie M

Betriebsdruck: -0,95 – 25 bar
 Temperaturbereich: -20 °C bis +120 °C

Anschluss	L	SW	Artikel-Nr.	
			MS	MSV
G 1/8 i	4	14	410234	416190
G 1/4 i	4	17	410235	416191
G 1/4 i	6	22		
G 3/8 i	4,5	19	410236	416192
G 3/8 i	7	27		
G 1/2 i	5	27	410237	416193
G 1/2 i	8	32		
G 3/4 i	5	32	410238	
G 3/4 i	9	36		
G 1 i	6	41	410239	
G 1 i	10	46		



Muffe Serie M

Betriebsdruck: -0,95 – 25 bar
 Temperaturbereich: -20 °C bis +120 °C

Anschluss	L	SW	Artikel-Nr.	
			MS	MSV
M 5 i	12	8		
G 1/8 i	22	13	410290	
G 1/4 i	26	17	410291	
G 3/8 i	32	22	410292	
G 1/2 i	36	27	410293	
G 3/4 i	36	32	410294	
G 1 i	40	41	410295	