

Reduzierstück mit zylindrischem Außen- und Innengewinde

Typ 16 bar Messing	Gewinde außen	Gewinde innen	SW ¹⁾	L ¹⁾
	M 5	M 3	7	1,5
	M 5	G 1/8"	14	12,0
	G 1/8"	M 5	14	4,0
	G 1/8"	G 1/4"	17	18,0
	G 1/8"	G 3/8"	19	19,0
	G 1/8"	G 1/2"	---	---
	G 1/4"	M 5	17	4,0
410320	G 1/4"	G 1/8"	17	4,0
	G 1/4"	G 3/8"	19	20,0
	G 1/4"	G 1/2"	24	14,0
410321	G 3/8"	G 1/8"	19	4,0
410323	G 3/8"	G 1/4"	19	5,0
	G 3/8"	G 1/2"	24	16,0
410322	G 1/2"	G 1/8"	24	6,0
410324	G 1/2"	G 1/4"	24	6,0
410326	G 1/2"	G 3/8"	24	6,0
	G 1/2"	G 3/4"	32	19,0
410329	G 3/4"	G 1/4"	27	5,0
410330	G 3/4"	G 3/8"	32	6,0
410331	G 3/4"	G 1/2"	32	8,0
	G 3/4"	G 1"	36	15,0
410335	G 1"	G 1/2"	36	6,0
410336	G 1"	G 3/4"	36	6,0
	G 1"	G 1 1/4"	45	14,0
	G 1 1/4"	G 3/4"	42	7,0
410341	G 1 1/4"	G 1"	42	7,0
	G 1 1/4"	G 1 1/2"	51	15,0
	G 1 1/2"	G 3/4"	50	8,0
410350	G 1 1/2"	G 1"	50	8,0
410351	G 1 1/2"	G 1 1/4"	50	8,0
	G 2"	G 1"	60	9,0
	G 2"	G 1 1/4"	60	9,0
	G 2"	G 1 1/2"	60	9,0

¹⁾ Angaben gelten für Typ Messing. Für alle anderen Typen fragen Sie bitte an.

