

Printing date 27.03.2019

\*

×

Version number 49

Revision: 20.03.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking		
· 1.1 Product identifier		
· Trade name: <u>Alupasten</u> -Spray		
<ul> <li>Article number: LOS430</li> <li>1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.</li> <li>Application of the substance / the mixture Lubricant</li> </ul>		
<ul> <li>1.3 Details of the supplier of the safety data sheet</li> <li>Manufacturer/Supplier: EURO-LOCK Vertriebs-GmbH Nordweststraß 3</li> <li>D-59387 Ascheberg</li> <li>Tel.: +49 (0) 2593 95887-0</li> <li>Fax.: +49 (0) 2593 95887-29</li> <li>www.euro-lock.de</li> <li>Further information obtainable from: +49 (0) 2593 95887-0</li> <li>E-Mail: info@euro-lock.de</li> <li>1.4 Emergency telephone number: +49 (0) 2593 95887-0 Monday - Thursday 8:00 - 17:00 CET, Friday 8:00 - 13:00 CET</li> </ul>		
SECTION 2: Hazards identification		
<ul> <li>2.1 Classification of the substance or mixture</li> <li>Classification according to Regulation (EC) No 1272/2008</li> <li>GHS02 flame</li> <li>Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.</li> </ul>		
$\mathbf{\nabla}$		
Skin Irrit. 2H315Causes skin irritation.Asp. Tox. 1H304May be fatal if swallowed and enters airways.		
Aquatic Chronic 3 H412Harmful to aquatic life with long lasting effects.		
<ul> <li>2.2 Label elements</li> <li>Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.</li> <li>Hazard pictograms</li> <li>GHS02 GHS07</li> </ul>		
· Signal word Danger		
<ul> <li>Signal word Danger</li> <li>Hazard-determining components of labelling: Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cycloalkanes, &lt; 5 % n-hexane White mineral oil, petroleum</li> <li>Hazard statements H2222 H220 Extermely flammable concel. Dresswiged container: May byret if bested</li> </ul>		

- H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
- H315 Causes skin irritation.
- H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 2)

<sup>-</sup> GB



Version number 49

Revision: 20.03.2019

Trade name: Alupasten-Spray

(Contd. of page 1)

• **Precautionary statements** P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P280 Wear protective gloves / eye protection / face protection.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

P501 Dispose of contents/container to hazardous or special waste collection point.

 $\cdot$  Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

- · 2.3 Other hazards
- $\cdot$  Results of PBT and vPvB assessment
- · **PBT:** Not applicable.

• **vPvB:** Not applicable.

#### **SECTION 3: Composition/information on ingredients**

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

#### · Dangerous components:

· Dangerous components.		
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane Flam. Gas 1, H220; Press. Gas (Comp.), H280	25-<50%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane Flam. Gas 1, H220; Press. Gas (Comp.), H280	10-<20%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	butane Flam. Gas 1, H220; Press. Gas (Comp.), H280	5-<10%
EC number: 927-510-4 Reg.nr.: 01-2119475515-33-xxxx	Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	5-<10%
EC number: 921-024-6 Reg.nr.: 01-2119475514-35-xxxx	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cycloalkanes, < 5 % n-hexane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	5-<10%
• Additional information: For the	wording of the listed hazard phrases refer to section 16.	

Additional information: For the wording of the listed hazard phrases refer to section 16.

#### **SECTION 4: First aid measures**

#### · 4.1 Description of first aid measures

· After inhalation:

Supply fresh air; consult doctor in case of complaints.

Take affected persons into fresh air and keep quiet.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Immediately remove any clothing soiled by the product.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

• After swallowing: Do not induce vomiting; call for medical help immediately.

(Contd. on page 3)

GB

Printing date 27.03.2019

. . ~



Version number 49

Revision: 20.03.2019

(Contd. of page 2)

Trade name: Alupasten-Spray

Printing date 27.03.2019

· 4.2 Most important symptoms and effects, both acute and delayed

Breathing difficulty

Headache Dizziness

Dizziness

Coughing

Nausea

 $\cdot$  **4.3 Indication of any immediate medical attention and special treatment needed** If swallowed or in case of vomiting, danger of entering the lungs.

Later observation for pneumonia and pulmonary oedema.

# **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- Suitable extinguishing agents:
- Foam

Fire-extinguishing powder

Carbon dioxide

- For safety reasons unsuitable extinguishing agents: Water with full jet
- $\cdot$  5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

- · 5.3 Advice for firefighters
- Protective equipment: Wear self-contained respiratory protective device.
- · Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

## **SECTION 6: Accidental release measures**

• 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation Keep away from ignition sources.

• 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

• 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

 $\cdot$  6.4 Reference to other sections See Section 13 for disposal information.

## **SECTION 7: Handling and storage**

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Avoid contact with skin and eyes.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke.
   Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

(Contd. on page 4)

GB



Printing date 27.03.2019

Version number 49

Revision: 20.03.2019

Trade name: Alupasten-Spray

(Contd. of page 3)

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:

· Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

· Information about storage in one common storage facility: Not required.

• Further information about storage conditions: Protect from heat and direct sunlight.

• 7.3 Specific end use(s) Industrial use.

## **SECTION 8: Exposure controls/personal protection**

• Additional information about design of technical facilities: No further data; see item 7.

#### • Ingredients with limit values that require monitoring at the workplace:

CAS: 106-97-8 butane WEL Short-term value: 1810 mg/m<sup>3</sup>, 750 ppm Long-term value: 1450 mg/m<sup>3</sup>, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

• **Respiratory protection:** Use suitable respiratory protective device in case of insufficient ventilation.

· Recommended filter device for short term use: Filter AX

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- Material of gloves
- Nitrile rubber, NBR

Recommended thickness of the material:  $\geq 0.45$  mm

- · Penetration time of glove material
- ≥240 min

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

Tightly sealed goggles

· Body protection: Protective work clothing

9.1 Information on basic physical and chemical properties General Information		
Appearance:		
Form:	Aerosol	
Colour:	Grey	
Odour:	Petrol-like	



Printing date 27.03.2019

Version number 49

Revision: 20.03.2019

Trade name: Alupasten-Spray

		(Contd. of page 4)
· Odour threshold:	Not determined.	
· pH-value:	Not determined.	
<ul> <li>Change in condition Melting point/freezing point: Initial boiling point and boiling range</li> </ul>	Undetermined. : < 0 °C	
· Flash point:	Not applicable, as aerosol.	
· Flammability (solid, gas):	Not applicable.	
· Ignition temperature:	>200 °C	
· Decomposition temperature:	Not determined.	
· Auto-ignition temperature:	Not determined.	
· Explosive properties:	Not determined.	
· Explosion limits: Lower: Upper:	Not determined. Not determined.	
· Vapour pressure:	Not determined.	
<ul> <li>Density at 20 °C:</li> <li>Relative density</li> <li>Vapour density</li> <li>Evaporation rate</li> </ul>	0.67912 g/cm <sup>3</sup> Not determined. Not determined. Not applicable.	
<ul> <li>Solubility in / Miscibility with water:</li> </ul>	Not miscible or difficult to mix.	
· Partition coefficient: n-octanol/water:	Not determined.	
<ul> <li>Viscosity:</li> <li>Dynamic:</li> <li>Kinematic:</li> <li>Organic solvents:</li> <li>VOC (EC)</li> </ul>	Not determined. Not determined. 64.2 % 436.1 g/l	
Solids content: • 9.2 Other information	0.0 % No further relevant information available.	

## **SECTION 10: Stability and reactivity**

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

Aldehyde

Carbon monoxide and carbon dioxide

(Contd. on page 6)



Printing date 27.03.2019

## Safety data sheet according to 1907/2006/EC, Article 31

Version number 49

Revision: 20.03.2019

Trade name: Alupasten-Spray

(Contd. of page 5)

## **SECTION 11: Toxicological information**

· 11.1 Information on toxicological effects

- Acute toxicity Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- $\cdot$  Skin corrosion/irritation
- Causes skin irritation.
- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- $\cdot$  Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- $\cdot$  CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- $\cdot$  Germ cell mutagenicity Based on available data, the classification criteria are not met.
- $\cdot$  Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- $\cdot$  STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard

May be fatal if swallowed and enters airways.

## **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:
- Harmful to aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

## **SECTION 13: Disposal considerations**

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue	
16 05 04*	gases in pressure containers (including halons) containing hazardous substances
15 01 04	metallic packaging

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

(Contd. on page 7)



Printing date 27.03.2019

\*

Version number 49

Revision: 20.03.2019

(Contd. of page 6)

Trade name: Alupasten-Spray

SECTION 14: Transport inform	ation
· 14.1 UN-Number	11811050
· ADR/RID/ADN, IMDG, IATA	UN1950
$\cdot$ 14.2 UN proper shipping name	
· ADR/RID/ADN	UN1950 AEROSOLS
· IMDG	AEROSOLS
· IATA	AEROSOLS, flammable
· 14.3 Transport hazard class(es)	
· ADR/RID/ADN	
· Class	2 5F Gases.
· Label	2.1
· IMDG, IATA	
· Class	2.1
· Label	2.1
· 14.4 Packing group · ADR/RID/ADN, IMDG, IATA	Void
· 14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user	Warning: Gases.
· Danger code (Kemler):	-
· EMS Number:	F-D,S-U
· Stowage Code	SW1 Protected from sources of heat.
	SW22 For AEROSOLS with a maximum capacity o
	litre: Category A. For AEROSOLS with a capacity abo
	1 litre: Category B. For WASTE AEROSOLS: CATEGORY B. FOR WASTE AEROSOLS; FOR WASTE
	C, Clear of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity o
	litre: Segregation as for class 9. Stow "separated fro
	class 1 except for division 1.4. For AEROSOLS wit
	capacity above 1 litre: Segregation as for the appropri
	subdivision of class 2. For WASTE AEROSOI Segregation as for the appropriate subdivision of class 2
• 14.7 Transport in bulk according to An Marpol and the IBC Code	nex II of Not applicable.
• Transport/Additional information:	
· ADR/RID/ADN	11
• Limited quantities (LQ) Excented quantities (EQ)	1L Code: E0
· Excepted quantities (EQ)	Not permitted as Excepted Quantity
· Transport category	2

GB



Printing date 27.03.2019

Version number 49

Revision: 20.03.2019

Trade name: Alupasten-Spray

(Contd. of page 7)

GR

IMDG
 Limited quantities (LQ)
 Excepted quantities (EQ)

1L Code: E0 Not permitted as Excepted Quantity

· UN "Model Regulation":

UN 1950 AEROSOLS, 2.1

## **SECTION 15: Regulatory information**

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P3a FLAMMABLE AEROSOLS

· Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t

• Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Department issuing SDS: Product Safety department.

#### · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1: Flammable gases - Category 1 Aerosol 1: Aerosols - Category 1 Press. Gas (Comp.): Gases under pressure - Compressed gas Flam. Liq. 2: Flammable liquids - Category 2 Skin Irrit. 2: Skin corrosion/irritation - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3 • \* Data compared to the previous version altered.