EASYCUT K25

10 → 25 A

Ref. 068063



The EASYCUT K25 plasma cutter, without high-frequency (HF) ignition, cuts easily through all types of metal up to 8 mm thick. Its built-in compressor makes it ideal for a outdoor or remote working where only an electricity supply is available.

Built-in air compressor

In situations where the welder does not have access to compressed air, the EASYCUT K25 is a perfect solution for enabling outdoor work with its built-in compressor.

Quality cutting without distortion

The use of plasma ensures high-quality cuts even on painted structures:


- up to 8 mm for steel, stainless steel and cast iron.
- up to 6 mm for aluminium and copper.



Featuring the «Pilot Arc» system, the arc is initiated without having to touch the workpiece. This non-HF ignition system avoids all electromagnetic interference (from radios, computers, telephones or from medical equipment, etc.).

Easy, quick and safe to use

- The TPT25 torch (4 m) is equipped with a trigger safety device to prevent accidental or unintentional activation.
- Detachable torch and earth clamp allowing for easy transport.
- Built-in compressor (sound level: 60/70 dB).
- Duty cycle of 25 A @ 35%.



C € - EN 60974-1



Comes with	2 m 10 mm²	TPT 25 4 m		
ref. 068063	✓	✓		

PERFORMANCE							
Capacity	Thickness						
Separation							
Fe	8 mm						
Clean Cut							
Fe	6 mm						

ACCESSORIES & CONSUMABLES





TPT25 consumables kit 070721







PLASMA 600 trolley 040298

-[AM]-		I2	max 1 Max cut		max 1 Clean cut		EN 60974-1 (40°C)	↓	<u>•</u>	IP	
50/60 Hz	Α	Α	Acier Steel	Alu	Acier Steel	Alu	X (40°C)	cm	kg		
230V 1~	16	10 → 25	8	6	6	4	15 A @ 60% 25 A @ 35%	41 x 36 x 20	15	IP21S	