



COD.	DN	D1	D2	L1	L2	M	H	SW2
G2210PC100	15	Ø15	Rp 1/2"	107	58	45	56	34
G2210PC200	15	Ø18	Rp 3/4"	107	58	45	56	41
G2210PC300	20	Ø22	Rp 3/4"	118	63	45	58	48

Body: hot pressed brass CW617N
 Surface finishing: sandblasted
 Ball: **Brassed**
 Ball Seals: PTFE
 Handle: **Push and Turn, Yellow Polyamide**
 Thermo activated safety device Firebag®: cartridge installed into the valve Inlet

TECHNICAL SPECIFICATIONS

reference standard valve:	EN 331 - DVGW G5614 - DIN 3586
working pressure:	MOP 5
working temperature:	-20 °C +60 °C
heat resistance FIREBAG®:	HTB GT1 650 °C x 30'
intervention temp. FIREBAG®:	100 °C - 5K
Connections:	Threaded according to EN 10226-1
fields of use:	for all types of Gas as specified in EN 437 and DVGW G260/1 (methane, butane, propane).



	Denominazione / Designation	Code / Code	Rev.	Data / Date
	Gas Ball valve Pressfitting/F with thermo activated safety device	ST_G2T03		02/01/2017

Il presente disegno a termini di legge non può essere reso pubblico o riprodotto senza la nostra autorizzazione / this drawing to the law can not be published or reproduced without our permission © 2012 TECO s.r.l.