## PRODUCT DATA SHEET

# MASKING TAPE GOLD PLUS

### 1. DESCRIPTION :

Masking tape Gold Plus is intended for long term use on a variety of surfaces thanks to its special high performance acrylic adhesive. The product has a strong but thin carrier which provides extra strength to the product and allows very sharp paintlines at the same time.

The tape provides the ideal combination of good bonding strength in process but at the same time an excellent removability after use.

## 2. APPLICATION :

The tape is suitable for masking on fragile and delicate surfaces during extended periods of time. Depending on the type of surface the removability can be guaranteed up to 6 months. The tape has a good high temperature performance up to 125°C for 1 hour and an excellent UV resistance up to 3 months depending on the final application.

### 3. CHARACTERISTICS :

Carrier	: Yellow "Japanese rice paper"
Adhesive	: Specialty acrylic
Total thickness [µm]	: 90
Adhesion to steel [N/25 mm]	: 3.75
Tensile strength [N/25 mm]	: 75
Elongation [%]	: 5.0

### 4. AVAILABLE SIZES :

Width [mm]	:	19, 25, 38 and 50. Other dimensions upon request.
Length [m]	:	50. Other dimensions upon request.
Core [mm]	:	3"

#### **5. CONDITIONS :**

Store in a cool dry place away form sunlight and direct heat sources. As far as the storage conditions are respected, the product is guaranteed 12 months.

#### 6. DISCLAIMER :

All statements, technical information and product recommendations are based on tests in our laboratories we believe to be reliable. In all cases the user should however determine the suitability of the product for his intended use and user assumes all risk and liability whatsoever in connection therewith. Neither seller or manufacturer shall be liable for any loss or damage - direct, incidental or consequential - arising from the use of the product. Details of testmethods are available on request.

N° 13/0213/00-1/1

REV: 14/06/11

DATE: 16/02/11