


DN	1/4"	3/8"	1/2"	3/4"	1"	1"1/4"	1"1/2"	2"
L	53.6	45.5	54.5	66	75	85	97	109
Ø	10	10	15	20	25	32	39	48
I	11.5	11.5	14	16	17	18	19	21
I ₂	8	10.5	12.5	14	15.5	16	17	18.5
H	43	43	44.5	49	55.5	72	77	83.5
M	92	92	92	92	115	150	150	150
PN	40							



IN ACCORDING TO DIRECTIVE 97/23/CE TAB. 6

STANDARD VALVE FEATURES

Working temperature : MIN. -10°C MAX. +100 °C
 Max pressure : 40 bar
 Threaded ends : ISO 228/1

SPECIAL EXECUTIONS ON REQUEST

O-Ring in : FP/EPDM/SILICONE/HNBR Seats: PTFE + 25% CARBOGRAPYTE/
 Valve : CR brass material PTFE + 25%GLASS
 Ball: AISI 316 steel/Cr brass/teflon ball Personal lever

We don't assume the responsibility if you use products which are not consistent with the material used for the construction of our valves.

To be used as a guide only, IDROSFER reserve the right to change these data without notice.

Ref.	Parts	Material	Q.ty
1	Body	EN12420-CW617N	1
2	Ball	EN12164-CW614N	1
3	Seat	P.T.F.E.	2
4	Pushrod	EN12164-CW614N	1
5	Gasket	P.T.F.E.	1
6	O-Ring	FPM (Viton)	1
7	Screw	UNI 7356-CB4FF	1
8	Nut	EN12164-CW614N	1
9	Sleeve	EN12420-CW617N	1
10	Lever	EN1011-DD13	1