

# Safety Data Sheet according to (EC) No 1907/2006

Page 1 of 13

SDS No.: 346906

V005.1 Revision: 17.06.2015

printing date: 05.04.2016

Replaces version from: 26.02.2015

LOCTITE 270 BO10ML EN/DE

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

LOCTITE 270 BO10ML EN/DE

#### **Contains:**

3,3,5 Trimethylcyclohexyl methacrylate 2,2'-Ethylenedioxydiethyl dimethacrylate Maleic acid Acetic acid, 2-phenylhydrazide

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Adhesive

## 1.3. Details of the supplier of the safety data sheet

Henkel AG & Co. KGaA

Henkelstr. 67

40589 Düsseldorf

Germany

Phone: +49 211 797 0 Fax-no.: +49 211 798 2009

ua-productsafety.uk@uk.henkel.com

## 1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

## **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

## Classification (CLP):

Skin irritation Category 2

H315 Causes skin irritation.

Serious eye irritation Category 2

H319 Causes serious eye irritation.

Skin sensitizer Category 1

H317 May cause an allergic skin reaction.

Specific target organ toxicity - single exposure Category 3

H335 May cause respiratory irritation. Target organ: respiratory tract irritation

# 2.2. Label elements

#### Label elements (CLP):

Hazard pictogram:



Signal word: Warning

**Hazard statement:** H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H335 May cause respiratory irritation.

**Precautionary statement:** \*\*\*For consumer use only: P101 If medical advice is needed, have product container or

label at hand. P102 Keep out of reach of children. P501 Dispose of waste and residues in

accordance with local authority requirements\*\*\*

**Precautionary statement:** P261 Avoid breathing vapours.

**Prevention** P280 Wear protective gloves.

**Precautionary statement:** P302+P352 IF ON SKIN: Wash with plenty of water.

**Response** P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

## 2.3. Other hazards

None if used properly.

# **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

## General chemical description:

Anaerobic adhesive

# Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	231-927-0	25- 50 %	STOT SE 3 H335 Skin Irrit. 2 H315 Eye Irrit. 2 H319
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	203-652-6 01-2119969287-21	5-< 10 %	Skin Sens. 1B H317
Cumene hydroperoxide 80-15-9	201-254-7	1-< 2,5 %	Acute Tox. 4; Dermal H312 STOT RE 2 H373 Acute Tox. 4; Oral H302 Org. Perox. E H242 Acute Tox. 3; Inhalation H331 Aquatic Chronic 2 H411 Skin Corr. 1B H314
Maleic acid 110-16-7	203-742-5 01-2119488705-25	0,1-< 1 %	Acute Tox. 4; Oral H302 Acute Tox. 4; Dermal H312 Skin Irrit. 2 H315 Skin Sens. 1 H317 Eye Irrit. 2 H319 STOT SE 3 H335
Acetic acid, 2-phenylhydrazide 114-83-0	204-055-3	0,1-< 1 %	Acute Tox. 3; Oral H301 Skin Irrit. 2 H315 Skin Sens. 1 H317 Eye Irrit. 2 H319 STOT SE 3; Inhalation H335 Carc. 2 H351
1,4-Naphthalenedione 130-15-4	204-977-6	100- < 250 PPM	Acute Tox. 3; Oral H301 Skin Irrit. 2; Dermal H315 Skin Sens. 1; Dermal H317 Eye Irrit. 2 H319 Acute Tox. 1; Inhalation H330 STOT SE 3; Inhalation H335 Aquatic Acute 1 H400 Aquatic Chronic 1 H410 M factor: 10

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

## **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

## 4.2. Most important symptoms and effects, both acute and delayed

SKIN: Redness, inflammation.

SKIN: Rash, Urticaria.

EYE: Irritation, conjunctivitis.

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

#### 4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

# **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

# Suitable extinguishing media:

Carbon dioxide, foam, powder

Fine water spray

## Extinguishing media which must not be used for safety reasons:

None known

### 5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx) can be released.

## **5.3.** Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

#### Additional information:

In case of fire, keep containers cool with water spray.

# **SECTION 6: Accidental release measures**

# ${\bf 6.1. \, Personal \, precautions, \, protective \, equipment \, and \, emergency \, procedures}$

Avoid skin and eye contact.

Ensure adequate ventilation.

## 6.2. Environmental precautions

Do not let product enter drains.

#### 6.3. Methods and material for containment and cleaning up

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

#### **6.4.** Reference to other sections

See advice in section 8

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Use only in well-ventilated areas.

Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation.

#### Hygiene measures:

Good industrial hygiene practices should be observed.

Do not eat, drink or smoke while working.

Wash hands before work breaks and after finishing work.

# 7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.

Store in a cool, well-ventilated place.

## 7.3. Specific end use(s)

Adhesive

# **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

## **Occupational Exposure Limits**

Valid for

Great Britain

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Cumene 98-82-8 [CUMENE]	50	250	Short Term Exposure Limit (STEL):		EH40 WEL
Cumene 98-82-8 [CUMENE]			Skin designation:	Can be absorbed through the skin.	EH40 WEL
Cumene 98-82-8 [CUMENE]	25	125	Time Weighted Average (TWA):		EH40 WEL
Cumene 98-82-8 [CUMENE]	50	250	Short Term Exposure Limit (STEL):	Indicative	ECTLV
Cumene 98-82-8 [CUMENE]	20	100	Time Weighted Average (TWA):	Indicative	ECTLV

# $\label{eq:predicted} \textbf{Predicted No-Effect Concentration (PNEC):}$

Name on list	Environmental		Value				Remarks
	Compartment	period	mg/l	ppm	mg/kg	others	
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	aqua (freshwater)		8	11	8 8	0,164 mg/L	
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	aqua (marine water)					0,0164 mg/L	
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	STP					10 mg/L	
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	aqua (intermittent releases)					0,164 mg/L	
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	sediment (freshwater)				1,85 mg/kg		
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	sediment (marine water)				0,185 mg/kg		
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	Soil				0,274 mg/kg		
Maleic acid 110-16-7	aqua (freshwater)					0,074 mg/L	
Maleic acid 110-16-7	aqua (intermittent releases)					0,744 mg/L	
Maleic acid 110-16-7	sediment (freshwater)				0,0624 mg/kg		
Maleic acid 110-16-7	STP					3,33 mg/L	

# **Derived No-Effect Level (DNEL):**

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	Workers	inhalation	Long term exposure - systemic effects		48,5 mg/m3	
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	Workers	Dermal	Long term exposure - systemic effects		13,9 mg/kg bw/day	
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	general population	inhalation	Long term exposure - systemic effects		14,5 mg/m3	
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	general population	Dermal	Long term exposure - systemic effects		8,33 mg/kg bw/day	
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	general population	oral	Long term exposure - systemic effects		8,33 mg/kg bw/day	
Maleic acid 110-16-7	Workers	Dermal	Acute/short term exposure - local effects		0,55 mg/cm2	
Maleic acid 110-16-7	Workers	Dermal	Long term exposure - local effects		0,04 mg/cm2	
Maleic acid 110-16-7	Workers	Dermal	Acute/short term exposure - systemic effects		58 mg/kg bw/day	
Maleic acid 110-16-7	Workers	Dermal	Long term exposure - systemic effects		3,3 mg/kg bw/day	

# **Biological Exposure Indices:**

None

# 8.2. Exposure controls:

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly

ventilated area Filter type: A

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

Skin protection:

Appearance

Wear suitable protective clothing.

## **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

liquid liquid

Odor green characteristic

Odour threshold No data available / Not applicable

pH No data available / Not applicable

Initial boiling point >65 °C (>149 °F) Flash point 110 °C (230 °F)

Decomposition temperature No data available / Not applicable

Vapour pressure 2,85 mbar

(25 °C (77 °F))

Density 1,10 g/cm3

()

Bulk density
Viscosity
No data available / Not applicable
Viscosity
No data available / Not applicable
Viscosity (kinematic)
No data available / Not applicable
Explosive properties
No data available / Not applicable

Solubility (qualitative) Insoluble

(23 °C (73.4 °F); Solvent: Water)

Solubility (qualitative) Soluble

(Solvent: Acetone) Solidification temperature No data available / Not applicable Melting point No data available / Not applicable Flammability No data available / Not applicable Auto-ignition temperature No data available / Not applicable Explosive limits No data available / Not applicable Partition coefficient: n-octanol/water No data available / Not applicable No data available / Not applicable Evaporation rate Vapor density No data available / Not applicable Oxidising properties No data available / Not applicable

#### 9.2. Other information

No data available / Not applicable

V005.1

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Peroxides.

MSDS-No.: 346906

#### 10.2. Chemical stability

Stable under recommended storage conditions.

#### 10.3. Possibility of hazardous reactions

See section reactivity

#### 10.4. Conditions to avoid

No decomposition if used according to specifications.

## 10.5. Incompatible materials

See section reactivity

#### 10.6. Hazardous decomposition products

carbon oxides.

# **SECTION 11: Toxicological information**

#### 11.1. Information on toxicological effects

#### General toxicological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

## STOT-single exposure:

May cause respiratory irritation.

#### Oral toxicity:

May cause irritation to the digestive tract.

#### Inhalative toxicity:

Due to the low volatility of the product there are no hazards associated with inhalation under normal conditions of use

#### Skin irritation:

Causes skin irritation.

#### Eye irritation:

Causes serious eye irritation.

## Sensitizing:

May cause an allergic skin reaction.

#### Acute oral toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time		
2,2'-Ethylenedioxydiethyl	LD50	10.837 mg/kg	oral		rat	
dimethacrylate						
109-16-0						
Cumene hydroperoxide	LD50	550 mg/kg	oral		rat	
80-15-9						
Maleic acid	LD50	708 mg/kg	oral		rat	
110-16-7						

#### Acute inhalative toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time		

## Acute dermal toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time		
Maleic acid	LD50	1.560 mg/kg	dermal		rabbit	
110-16-7						

#### Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Cumene hydroperoxide 80-15-9	corrosive		rabbit	Draize Test

## Serious eye damage/irritation:

Hazardous components	Resu	ılt	Exposure	Species	Method
CAS-No.			time		
2,2'-Ethylenedioxydiethyl	slightly irritating		24 h	rabbit	OECD Guideline 405 (Acute
dimethacrylate					Eye Irritation / Corrosion)
109-16-0					

## Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of	Metabolic activation /	Species	Method
		administration	Exposure time		
Cumene hydroperoxide	positive	bacterial reverse	without		OECD Guideline 471
80-15-9		mutation assay (e.g			(Bacterial Reverse Mutation
		Ames test)			Assay)
Cumene hydroperoxide	negative	dermal		mouse	
80-15-9					

## Repeated dose toxicity

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
Cumene hydroperoxide		inhalation:	6 h/d 5 d/w	rat	
80-15-9		aerosol			

# **SECTION 12: Ecological information**

## General ecological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

# 12.1. Toxicity

# **Ecotoxicity:**

Do not empty into drains / surface water / ground water.

MSDS-No.: 346906

V005.1

Hazardous components	Value	Value	Acute	Exposure	Species	Method
CAS-No.	type		Toxicity Study	time		
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	LC50	16,4 mg/l	Fish	96 h		OECD Guideline 203 (Fish, Acute Toxicity Test)
Cumene hydroperoxide 80-15-9	LC50	3,9 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Cumene hydroperoxide 80-15-9	EC50	18 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Cumene hydroperoxide 80-15-9	ErC50	3,1 mg/l	Algae	72 h	Pseudokirchnerella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Maleic acid 110-16-7	LC50	> 245 mg/l	Fish	48 h	Leuciscus idus	DIN 38412-15
Maleic acid 110-16-7	EC50	42,81 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
1,4-Naphthalenedione 130-15-4	EC50	0,011 mg/l	Algae	72 h	Dunaliella bioculata	OECD Guideline 201 (Alga, Growth Inhibition Test)

# 12.2. Persistence and degradability

# **Persistence and Biodegradability:** No data available.

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	readily biodegradable		85 %	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Cumene hydroperoxide 80-15-9		no data	0 %	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Maleic acid 110-16-7	readily biodegradable	aerobic	97,08 %	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
1,4-Naphthalenedione 130-15-4		no data	0 - 60 %	OECD 301 A - F

# 12.3. Bioaccumulative potential / 12.4. Mobility in soil

# **Mobility:**

Cured adhesives are immobile.

## **Bioaccumulative potential:**

No data available.

Hazardous components	LogKow Bioconcentration	Exposure	Species	Temperature	Method
CAS-No.	factor (BCF)	time			

V005.1

2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	1,88				
Cumene hydroperoxide 80-15-9	2,16	9,1	calculation		OECD Guideline 305 (Bioconcentration: Flow- through Fish Test)
Cumene hydroperoxide 80-15-9	2,10				
Maleic acid 110-16-7	-1,3			20 °C	OECD Guideline 107 (Partition Coefficient (noctanol / water), Shake Flask Method)
Acetic acid, 2- phenylhydrazide 114-83-0	0,74				
1,4-Naphthalenedione 130-15-4	1,71				

## 12.5. Results of PBT and vPvB assessment

Hazardous components	PBT/vPvB
CAS-No.	
2,2'-Ethylenedioxydiethyl dimethacrylate	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
109-16-0	Bioaccumulative (vPvB) criteria.
Maleic acid	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
110-16-7	Bioaccumulative (vPvB) criteria.

## 12.6. Other adverse effects

No data available.

## **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

Product disposal:

Dispose of in accordance with local and national regulations.

Contribution of this product to waste is very insignificant in comparison to article in which it is used

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

#### Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

## **SECTION 14: Transport information**

## 14.1. UN number

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

## 14.2. UN proper shipping name

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

#### 14.3. Transport hazard class(es)

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

## 14.4. Packaging group

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

#### 14.5. Environmental hazards

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

## 14.6. Special precautions for user

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

## 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

## **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC content (2010/75/EC) < 3 %

# 15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

V005.1

MSDS-No.: 346906

## **SECTION 16: Other information**

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

- H242 Heating may cause a fire.
- H301 Toxic if swallowed.
- H302 Harmful if swallowed.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.
- H331 Toxic if inhaled.
- H335 May cause respiratory irritation.
- H351 Suspected of causing cancer.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.

#### **Further information:**

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

#### Label elements (DPD):

## Xi - Irritant



#### Risk phrases:

R36/37/38 Irritating to eyes, respiratory system and skin.

R43 May cause sensitisation by skin contact.

# Safety phrases:

- S23 Do not breathe vapour.
- S24/25 Avoid contact with skin and eyes.
- S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- S37 Wear suitable gloves.

#### Additional labeling:

For consumer use only: S2 Keep out of the reach of children.

S46 If swallowed, seek medical advice immediately and show this container or label.

#### Contains:

Maleic acid,

2,2'-Ethylenedioxydiethyl dimethacrylate

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.