

Bestellung
ASV-PV-Ventil für den hydraulischen Abgleich, einschließlich:
 Steuerleitung, 1,5 m (G 1/16 A)

Typ	DN	K _{vs} (m ³ /h)	Anschluss		Δp-Einstellbereich (kPa)	Bestell-Nr.	
						ohne Isolierung	mit EPP-Isolierung
	15	1,6	Innengewinde ISO 7/1	R _p 1/2	5-25		003Z5601
	20	2,5		R _p 3/4		003Z5602	
	25	4,0		R _p 1		003Z5603	
	32	6,3		R _p 1 1/4		003Z5604	
	40	10,0		R _p 1 1/2		003Z5605	
	50	16,0		R _p 2		003Z5606	
	15	1,6	Außengewinde ISO 228/1	G 3/4 A	5-25		003Z5611
	20	2,5		G 1 A		003Z5612	
	25	4,0		G 1 1/4 A		003Z5613	
	32	6,3		G 1 1/2 A		-	
	40	10,0		G 1 3/4 A		-	
	50	16,0		G 2 1/4 A		-	
	15	1,6	Innengewinde ISO 7/1	R _p 1/2	20-60	003Z5541	-
	20	2,5		R _p 3/4		003Z5542	
	25	4,0		R _p 1		003Z5543	
	32	6,3		R _p 1 1/4		003Z5544	
	40	10,0		R _p 1 1/2		003Z5545	
	50	16,0		R _p 2		003Z5546	
	15	1,6	Außengewinde ISO 228/1	G 3/4 A	20-60	003Z5551	-
	20	2,5		G 1 A		003Z5552	
	25	4,0		G 1 1/4 A		003Z5553	
	32	6,3		G 1 1/2 A		003Z5554	
	40	10,0		G 1 3/4 A		003Z5555	
	50	16,0		G 2 1/4 A		003Z5556	

ASV-BD, multifunktionales Partnerventil (Absperung, drehbare Messeinheit) und EPP-Isolierung

Typ	DN	K _{vs} (m ³ /h)	Anschluss	Bestell-Nr.
	15	3,0	Innen- gewinde ISO 7/1	R _p 1/2 003Z4041
	20	6,0		R _p 3/4 003Z4042
	25	9,5		R _p 1 003Z4043
	32	18		R _p 1 1/4 003Z4044
	40	26		R _p 1 1/2 003Z4045
	50	40		R _p 2 003Z4046

ASV-M, ohne Messnippel und mit EPS-Isolierung

Typ	DN	K _{vs} (m ³ /h)	Anschluss	Bestell-Nr.
	15	1,6	Innen- gewinde ISO 7/1	R _p 1/2 003L7691
	20	2,5		R _p 3/4 003L7692
	25	4,0		R _p 1 003L7693
	32	6,3		R _p 1 1/4 003L7694
	40	10		R _p 1 1/2 003L7695
	15	1,6	Außen- gewinde ISO 228/1	G 3/4 A 003L7696
	20	2,5		G 1 A 003L7697
	25	4,0		G 1 1/4 A 003L7698
	32	6,3		G 1 1/2 A 003L7699
	40	10		G 1 3/4 A 003L7700
50	16	G 2 1/4 A 003L7702		