



Product Information Sheet



Panasonic		WARMER						AVERAGE						COLDER					
Indoor Unit	Outdoor Unit	P _{rated}	η _s	Q _{IE}	P _{sup}	A+++ ~ D	A+++ ~ D	P _{rated}	η _s	Q _{IE}	dB(A) (55°C) *2	dB(A) (55°C) *2	dB(A) (55°C) *2	dB(A) (55°C) *2	P _{sup}	P _{rated}	η _s	Q _{IE}	P _{sup}
		kW (35/55°C)	% (35/55°C)	kWh (35/55°C)	kW	35°C	55°C	kW (35/55°C)	% (35/55°C)	kWh (35/55°C)	dB(A) (55°C) *2	dB(A) (55°C) *2	dB(A) (55°C) *2	dB(A) (55°C) *2	kW	kW (35/55°C)	% (35/55°C)	kWh (35/55°C)	kW
*1	WH-MXC09J8E8	9/9	256% / 171%	1859 / 2772	3	A+++	A++	9/9	195% / 140%	3747 / 5208	-	68	-	65	3	11/11	169% / 127%	6289 / 8327	3
*1	WH-MXC12J9E8	9/9	256% / 171%	1859 / 2772	9	A+++	A++	9/9	195% / 140%	3747 / 5208	-	69	-	65	9	11/11	169% / 127%	6289 / 8327	9
*1	WH-MXC16J9E8	16/16	232% / 160%	3634 / 5230	9	A+++	A++	13/16	176% / 129%	6018 / 9984	-	72	-	66	9	19/18	150% / 125%	12233/13870	9

811/2013

*1

R32 (GWP=675)

Refrigerant leakage contributes to climates change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 675. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 675 times higher than 1 kg of CO₂, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.

*2

Maximum A-Weighted Sound Power Level (L_{WA}), according to EN12102-1 at A7(6) W55(47), in dB (A).

*3

Nominal A-Weighted Sound Power Level (L_{WA}), according to regulation 811/2013, 813/2013 and standard EN14825 at A7(6), in dB (A).

Energy consumption "XYZ" kWh per year, based on standard test results.

Actual energy consumption will depend on how the appliance is used and where it is located.

- You can find information and precautions relevant for installation and maintenance in the Operation Instructions.
- You can find information relevant for recycling and/or disposal at end-of-life in the Operation Instructions.

ACXF71-01850